

Industrial Power Supply

GNT-IP52520WS

- IP40 Protection
- Four-Output
- Total 520W Power Supply


Product Features

- Aluminum shell for better heat dissipation, stable and durable
- For extreme temperature enviroments: -40°C~70°C
- Standard DIN-Rail mounting, fast in installation


Ports Description



Dimension (mm)



Installation Diagram



Specifications

Model	GNT-IP52520WS
Power Output	DC 52V 2.5A(Four-Output)
Power	520W
Ripple & Noise	Peak ≤1% (Typical 200mVp-p)
Time of Start-up & Rise	800ms, 20ms
Hold Time	60ms/12ms(Full Load)
Power Input	90~264VAC 50/60Hz
Input Current(Max)	6A
Average Output Efficiency	90%
Hipot Test	I/P-O/P:3KVAC I/P-FG:2KVAC O/P-FG:0.5KVAC
Insulation Resistance Test	I/P-O/P, I/P-FG, O/P-FG:100M Ohms / 500VDC / 25°C / 70%RH
Circuit Protection	Support
Over Current Protection	Support
Over Temperature Protection	Support
Protection Level	Protection Level:IP40, Lightning Protection:6KV, Per: IEC61000-4-5 ESD Protection:8KV, Per: IEC61000-4-2
Physical Specifications	Size(H*D*W): 145*110*88mm, Weight: 1.3KG/Pcs
Package	Size(L*W*H): 400*360*230mm(CTN Box); 12Pcs/CTN
Working Environment	Operating Temperature: -40°C~70°C
	Storage Temperature: -40°C~70°C
	Relative Humidity: 10%~90% Non-condensing
	Heat dissipation mode: Fan design
Certification	CE Mark
	FCC Part15,Class B
	RoHS 2.0
Warranty	Whole Device: 1 year
Package Content	User Manual