

Industrial-Grade Surge Protection

GNT-SP16AL4-H

- LED Status
- 16A 240VAC Max. 3000W
- Power Input: 220VAC

Product Features

- Delay Time On 30 Sec.(Default)
- Switch ON - OFF
- Button SET

Product Figure



Specifications

| | |
|---------------------|----------------------------------------------------------|
| Model | GNT-SP16AL4-H |
| Input Voltage | 220 VAC |
| Protection Range | Over voltage (OV) : 270 VAC |
| | Under voltage (UV) : 170 VAC |
| | Accuracy : ≤0.5% |
| LED | Status normally, Over Voltage, Under Voltage, Delay time |
| Time | Delay off : 1 - 210 Sec. |
| | Delay on : 5 - 180 Sec. |
| | Relay reset : Automatic |
| Power | Output : 16A 240 VAC |
| | Cable 3 x 1.5 SQ.mm. |
| | Max. 3000W |
| Working Environment | Operating Temperature: -10°C~55°C |
| | Storage Temperature: -10°C~55°C |
| | Operating Humidity: 10%~90% Non-condensing |
| | Storage Humidity: 5%~90% Non-condensing |
| Protection | IP:20 |
| Dimensions | 65.8 x 110.3 x 271.5 mm. |
| Warranty | Whole Device: 1 year |
| Package Content | User Manual |

Key Feature

Protect electrical equipment from voltage drops, overvoltages, and surges.

There is an LED to indicate the working status.

Adjust to set delay time.

Delay 30 Sec. Will activated to capture the electrical signal working at 200V to prevent severe electrical surges.