

AI 24V PoE Switch

GNT-9828-4

- Total 120W Power Supply
- 8 ports 24V PoE (4&5+7;&8-)
- 2 ports Uplink

Product Features


- AI Watchdog Function
- 6KV Lightning & 8KV ESD Protection

Ports Description




- ① 100Mbps PoE Ports
- ② 100Mbps Uplink Ports

Dimension (mm)



Installation Diagram



Specifications

Model	GNT-9828-4
Ports	PoE (1~8):10/100Mbps PoE ports (RJ45) LAN(1~2):10/100Mbps uplink ports (RJ45)
Transmission Rate	200Mbps Full Duplex; 10 or 100Mbps Half Duplex
Transmission Distance	130m
Performance Specification	Bandwidth:2.0Gbps Network Latency (10 to 100Mbps): $\leq 16\mu s$ (use the 64byte package size) MAC address table: 2K The Frame Filter & Transmission Rate: 14800pps the most for 10M port, 148800pps the most for 100M port
Networking Standard	IEEE 802.3i 10BASE-T IEEE 802.3u 100BASE-TX IEEE 802.3x Flow Control IEEE 802.3af Power over Ethernet
Power Support	Power Input: AC 90~240V Total $\leq 120W$ AI Watchdog: Port 1~8 Power Output: PoE 1~8 Port:4/5(+24V),7/8(GND) $\leq 15W$
Protection Level	Lightning Protection: 6KV ESD Protection: 8KV
Physical Specifications	Size(L*W*H): 190mm*140mm*43mm, Weight: 1.0KG
Working Environment	Operating Temperature: -30°C~60°C Storage Temperature: -40°C~70°C Operating Humidity: 10%~90% Non-condensing Storage Humidity: 5%~90% Non-condensing
Certification	CE FCC RoHS 2.0
Warranty	Whole Device: 1 year
Package Content	AC Power Cable,User Manual