

# Intelligent PoE Splitter

## GNT-69P01

- Support IEEE 802.3af PoE
- Wide voltage 38~57V
- Electronic isolation


## Product Features

- Power indicator light
- 6KV lightning & 8KV ESD protection

## Ports Description



## Dimension (mm)



## Specifications

|                          |                                                              |
|--------------------------|--------------------------------------------------------------|
| Model                    | GNT-69P01                                                    |
| Product Description      | Intelligent PoE splitter                                     |
| PoE Standard             | IEEE802.3af Power over Ethernet                              |
| Input Port               | 1*10/100Mbps RJ45, Support 1236/4578                         |
| Data Output              | 1*10/100Mbps RJ45, Data PIN(1/2,3/6), 4/5(Empty), 7/8(Empty) |
| Power Output             | 5521 DC, DC12V, With power indicator light                   |
| Short Circuit Protection | Support                                                      |
| Constant Current Output  | Support                                                      |
| Maximum Output Power     | 14W                                                          |
| Physical Specifications  | Size(L*W*H): 240*24*27mm, Weight: 0.05KG                     |
| Working Environment      | Operating Temperature: -30°C~60°C                            |
|                          | Storage Temperature: -40°C~70°C                              |
|                          | Operating Humidity: 10%~90% Non-condensing                   |
|                          | Storage Humidity: 5%~90% Non-condensing                      |
| Certification            | CE                                                           |
|                          | FCC                                                          |
|                          | RoHS 2.0                                                     |
| Warranty                 | Whole Device: 1 year                                         |

## Installation Diagram:

