

Cloud L2 Gigabit Managed Industrial Switch

GNT-IS308D-P

- Total Power 110W
- RJ45(PoE) * 8

Product Features


- Support Web management
- Support port 250 meters transmission (10Mbps)

Ports Description




1 1000Mbps PoE Ports

Dimension (mm)



Installation Diagram



Specifications

Model	GNT-IS308D-P
Ports	PoE(1~8):10/100/1000Mbps PoE(RJ45)
Power Supply	Power Input:AC100~240V; Total power ≤ 110W
Networking Standard	IEEE 802.3i 10BASE-T/IEEE 802.3u 100BASE-TX IEEE 802.3ab 1000BASE-T IEEE 802.3x Flow Control IEEE 802.3af/at Power over Ethernet
Web Management	Factory IP: 192.168.1.253 Default password: admin
Indicator Light	Per RJ45 Ports: LINK/ACT(Green:1000M/Yellow:100/10M)
MAC Address	Support MAC Address Binding; Support MAC Address Searching; Support MAC Address Learning;
VLAN	Support 802.1Q VLAN; Support Hybrid VLAN Mode;
Port	Support port flow control; Support port speed and Duplex configuration; Support port Adaptive MDI/MDI-X; Support port 250 meters transmission (10Mbps);
DHCP	Support DHCP Client;
Management Features	Support Web-based Management(HTTP); Support Cloud Management;
Jumbo Frame	9Kbytes
Switching Capacity	16Gbps
Packet Forwarding Rate	11.9Mpps
MAC Capacity	2K
Flash	16MB
Protection Level	Lightning Protection:6KV; ESD Protection:8KV;
Physical Specifications	Size(L*W*H): 145mm* 110mm* 51mm; Weight: 0.6KG;
Environment	Operating Temperature: -40°C~70°C Storage Temperature: -40°C~70°C Operating Humidity: 10%~90% Non-condensing Storage Humidity: 5%~90% Non-condensing
Certification	CE, FCC, RoHS 2.0
Warranty	1-year Warranty
Package Content	Switch * 1; Power Cable; User Manual * 1;